

DECLARATION OF PERFORMANCE

- Unique identification code of the product-type:  
*CELSAMAX Weldable, ribbed, hot rolled reinforcing steel in coils in steel quality B500SP (PN-H-93220:2006 and MSZ/T 339:2012.03) with  $R_e \geq 500$  MPa declared yield strength calculated from nominal cross-section, in nominal diameters  $\varnothing 10, \varnothing 12, \varnothing 14, \varnothing 16$  mm*
- Type, batch or serial number or any other element allowing identification of the construction product according to government decree no. 275/2013 (issued on 16<sup>th</sup> July):  
  
*Rolling mark applied on the product: 1-17*
- Intended use or uses of the construction product, in accordance with the relevant technical approval, as foreseen by the manufacturer:  
*The reinforcing steel products may be used as reinforcement of concrete structures according to EN 10080:2005, in steel quality B500SP (PN-H-93220:2018 and MSZ/T 339:2012.03).  
 The steel bars can be taken into account with the parameters of B 60.50 (MSZ 339:1987) steel by performing diagnostic works on building designed in accordance with **withdrawn** standards no. MSZ 15022:1986 and no. MSZ 15022:1986/1M:1992.  
 The steel bars can be taken into account as product in ductility class C with  $R_{eH} = 500$  MPa declared yield strength calculated from nominal cross-section at design works and strength calculations, according to Annex C of standard no. EN 1992-1-1:2004 + EN 1992-1-1:2004/ AC:2010 (EUROCODE 2)..*
- Name, registered trade name or registered trade mark and contact address of the manufacturer:  
*CELSA "Huta Ostrowiec" Sp. z o.o.  
 ul. Samsonowicza 2, PL-27-400 Ostrowiec Świętokrzyski, Poland*
- System or systems of assessment and verification of constancy of performance of the construction product:  
 System (1+)
- ÉMI Non-profit Ltd. for Quality Control and Innovation In Building, **H-2000 Szentendre, Dózsa György út 26**, Hungary, who issued the National Technical Assessment no. A-80/2017 dated at 29.07.2019 is designated body who performed:
  - the determination of product type
  - the audit tests of random chosen samples,
  - the initial inspection of the factory and factory production control,
  - the continuous surveillance, verification and assessment of the factory production control in System (1+), and issued the Certificate of Conformity for the product with no. 20-CPR-249-(C-4/2007) dated at 05.02.2020

7. Declared performance

Essential characteristics	Performance	Applied test and product standards	Technical specification
Yield or proof strength ( $R_{eH}$ or $R_{p0,2}$ )	$\geq 485$ MPa (individual) 500÷625 MPa (characteristic)	MSZ EN 1992-1-1:2010 MSZ EN 10080:2005 MSZ/T 339:2012.03 MSZ 339:1987 <b>PN-H-93220:2018</b> MSZ EN ISO 15630-1:2011 MSZ EN ISO 6892-1:2010	National Technical Assessment no. A-80/2017 dated at 29.07.2019
Tensile strength ( $R_m$ )	$\geq 582$ MPa (individual) $\geq 600$ MPa (characteristic)		
Stress ratio ( $R_m / R_e$ )	1,13÷1,38 (individual) 1,15÷1,35 (characteristic)		
Elongation ( $A_{gt}$ )	$\geq 6,75\%$ (individual) $\geq 8\%$ (characteristic)		
Elongation ( $A_5$ )	$\geq 18\%$ (average)		
Bendability Bending 90 degrees, Re-bending 20 degrees	$d \leq 12$ mm: 5d mandrel $12 < d \leq 16$ mm: 6d mandrel $16$ mm < d: 8d mandrel		
Reaction to fire	A1		
Tolerance of production length	+100 / -0 mm		
Tolerances from nominal cross-section	$d \leq 8$ mm: $\pm 6,0\%$ $d > 8$ mm: $\pm 4,5\%$		
Bonding strength ( $f_R$ )	$d = 8$ mm: 0,045 $8$ mm < $d \leq 10$ mm: 0.052 $d > 10$ mm: 0.056		
Weldability ( $C_{eq}$ ):	$C_{eq} \leq 0.52$		
Durability (product analysis):	$C \leq 0.24$ ; $S \leq 0.055$ ; $P \leq 0.055$ ; $N \leq 0.014$ ; $Cu \leq 0.85$ ; $C_{eq} \leq 0.52$		
Fatigue:	$\sigma_M = 300$ MPa; $2\sigma_A = 150$ MPa; $n = 2 \cdot 10^6$		

8. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 7.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Ostrowiec Świętokrzyski, 05.02.2020

  
.....  
(Stanisław Klusek)  
(Quality Manager of RPP)